

163T-LF Series

Class 125, PTFE Seat, NPT Swing Check

LEAD FREE



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The **lead free* Apollo® Model 163T-LF (61YLF Series) Swing Check** provides a reliable, long lasting, "Made in the USA" alternative to globally sourced check valves for potable water service. These valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials. The Apollo® swing check may be installed in either horizontal or vertical orientation with upward flow.

FEATURES

- Dezincification Resistant Bronze Construction
- Renewable PTFE Seat Disc
- 100% Factory Tested per MSS SP-139
- NPT Connection
- **Cast, Machined and Assembled in the USA**
- ARRA Compliant

PERFORMANCE RATING

- Cold Working Pressure:
200 psi (13.8 Bar) at 100°F
- SWP: 125 psi (8.6 Bar) at 353°F
- Temperature Range: -20°F to 406°F

APPROVALS

- MSS SP-80 Design & Tested
- MSS SP-139, "Copper Alloy Gate, Globe, & Check Valves"
- NSF/ANSI 372 Lead Free, 3rd Party Certified
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"
- CSA B51 CRN 0C14667.

PRECAUTIONARY NOTE:

Not recommended for applications which may induce pulsation or repetitive vibration. See Installation Manual for details.

STANDARD MATERIALS LIST

BODY	ASTM B584-C89836 Bronze
CAP	ASTM B584-C89836 Bronze
HANGER	304 Stainless Steel or ASTM B584 C89836 Bronze
PIN	304 Stainless Steel
JAM NUT	304 Stainless Steel
SEAT	PTFE
PLUG	UNS 27450 Lead Free* Brass

DIMENSIONS

MODEL NUMBER	PART NUMBER	SIZE (IN.)	HEIGHT (IN.)	LENGTH (IN.)	WEIGHT (LB.)	CV (GPM)
163T12LF	61YLF-203-T1	1/2"	1.65	2.48	.73	7.0
163T34LF	61YLF-204-T1	3/4"	1.9	2.94	1.06	12.0
163T1LF	61YLF-205-T1	1"	2.26	3.57	1.7	28.6
163T114LF	61YLF-206-T1	1-1/4"	2.99	4.50	3.3	39.0
163T112LF	61YLF-207-T1	1-1/2"	2.99	4.50	3.1	56.0
163T2LF	61YLF-208-T1	2"	3.74	5.25	5.4	152.0

Warning: Do not use in reciprocating compressor service.

*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law 111-380. ANSI 3rd party approved and listed.