



# Certificate of Compliance

**Certificate:** 2646937 (112384\_0\_000)

**Master Contract:** 187265

**Project:** 70051388

**Date Issued:** 2016-01-11

**Issued to:** Apollo Valves (Conbraco Industries, Inc.)  
1418 S Pearl St  
Pageland, South Carolina 29728  
USA

**Attention:** Stephen Vollentine

*The products listed below are eligible to bear the CSA Mark shown*



**Issued by:** *James Sekerak*  
James Sekerak

## PRODUCTS

CLASS - C337110 - VALVES (GAS)-Lever Operated Non-Lubricated Shutoff

For details related to rating, size, configuration, etc. reference should be made to the CSA Certification Record or the descriptive report.

**For Use with Natural, Mfd., Mixed, Liquefied Petroleum or Propane Gases and LP Gas-Air Mixtures**

**Straight Through**

**Model Number**

### **76-100 Series**

- 76-10101A, Rated Pressure: 125 psi, Inlet Size: ¼"
- 76-102-01A, Rated Pressure: 125 psi, Inlet Size: 3/8"
- 76-103-01A, Rated Pressure: 125 psi, Inlet Size: ½"
- 76-104-01A, Rated Pressure: 125 psi, Inlet Size: ¾"
- 76-105-01A, Rated Pressure: 125 psi, Inlet Size: 1"
- 76-106-01, Rated Pressure: 125 psi, Inlet Size: 1-1/4"
- 76-107-01, Rated Pressure: 125 psi, Inlet Size: 1-1/2"
- 76-108-01, Rated Pressure: 125 psi, Inlet Size: 2"
- 76-109-01, Rated Pressure: 125 psi, Inlet Size: 2-1/2"
- 76-100-01, Rated Pressure: 125 psi, Inlet Size: 3"



**Certificate:** 2646937  
**Project:** 70051388

**Master Contract:** 187265  
**Date Issued:** 2016-01-11

---

**76F-100 Series**

76F-101-(01,27), Rated Pressure: 125 psi, Inlet Size: 1/4"  
76F-102-(01,27), Rated Pressure: 125 psi, Inlet Size: 3/8"  
76F-103-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 1/2"  
76F-104-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 3/4"  
76F-105-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 1"  
76F-106-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 1-1/4"  
76F-107-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 1-1/2"  
76F-108-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 2"  
76F-100-(01,27)A, Rated Pressure: 125 psi, Inlet Size: 3"

**APPLICABLE REQUIREMENTS**

CSA/CAN 3.16-M88 (R-2014) – Lever Operated Non-Lubricated Gas Shut-Off Valves



## *Supplement to Certificate of Compliance*

**Certificate:** 2646937 (112384\_0\_000)

**Master Contract:** 187265

*The products listed, including the latest revision described below,  
are eligible to be marked in accordance with the referenced Certificate.*

### **Product Certification History**

<b>Project</b>	<b>Date</b>	<b>Description</b>
70051388	2016-01-11	Addition of valve options to Model Series 76 and 76F.
70048116	2015-10-19	Addition of Model 76F, Size 3-inch.
70020384	2015-02-12	Addition of locking handle option "-27" to Model Series 76F-100. Addition of Figures 82 to 90.
2646937	2013-10-16	Original certification of 76-100 Series and 76F-100 Series to CAN 3.16-M88. Addition of Figures 1 to 81.

**MASTER CONTRACT:** 187265  
**REPORT:** 2646937  
**PROJECT:** 70051388

**Date Issued:** January 11, 2016

---

The following options are available to all sizes except where indicated for Model Series 76:

<b>Suffix</b>	<b>Option</b>
-02	Stem Grounded
-04	2.25" Stem Extension
-07	Steel Tee Handle
-08	90° Reversed Stem
-14	Side Vented Ball (Uni-Directional)
-15	Steel Wheel Handle
-16	Vertical Chain Lever
-19	Pad-Locking Devices
-21	UHMWPE Trim (Non-PTFE)
-24	Graphite Packing
-27	SS Latch-Lock Handle and SS Nut
-30	Cam-Lock Handle and Grounded
-32	SS Tee Handle And Nut
-35	PTFE Trim
-39	SS Hi-Rise Locking Wheel Handle, SS Nut
-40	Cyl-Loc and Grounded
-44	Seal Welded
-45	Less Lever And Nut
-46	SS Lock Closed Only
-47	SS Latch-Lock Oval Handle
-48	SS Oval Handle (No Latch) & Nut
-49	No Lubrication. Assembled Dry.
-50	2.25" Locking Stem Extension
-56	Multifill Seats & Packing
-57	Oxygen Cleaned
-58	Chain Lever - Horizontal
-60	Grounded Ball And Stem
-64	250 psi SWP (Steam Working Pressure)

**MASTER CONTRACT:** 187265  
**REPORT:** 2646937  
**PROJECT:** 70051388

**Date Issued:** January 11, 2016

---

The following options are available to all sizes except where indicated for Model Series **76F**:

<b>Suffix</b>	<b>Option</b>
-02	Stem Grounded
-04	2.25" Stem Extension
-08	90° Reversed Stem
-11	Therma-Seal™ Insulating Tee Handle
-14	Side Vented Ball (Uni-Directional)
-24	Graphite Packing
-27	SS Latch-Lock Handle and SS Nut
-30	Cam-Lock Handle and Grounded
-32	SS Tee Handle And Nut
-39	SS Hi-Rise Locking Wheel Handle, SS Nut
-40	Cyl-Loc and Grounded
-45	Less Lever And Nut
-46	SS Lock Closed Only
-47	SS Latch-Lock Oval Handle
-48	SS Oval Handle (No Latch) & Nut
-56	Multifill Seats & Packing
-60	Grounded Ball And Stem