



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

The Model 899 End-All fitting is a unique domed end cap fitting available with a 1/2", 3/4" or 1" NPT or BSP threaded outlet. Designed as an end of line fitting, the End-All features two multi-function bosses which can be used for the direct connection of sprinkler heads, sprigs, drops, drains and or gauges. The Model 899 End-All fitting pressure ratings conform to the ratings of the coupling used to join the system.

For Fire Protection pressure rating, listing, and approval information, refer to Data Sheet B-42 or visit www.shurjoint.com for details or contact Shurjoint.

DIMENSIONS

NOMINAL SIZE GROOVED X THREADED	PIPE O.D.	THREADS	DIMENSIONS				WEIGHT
			X	Y	A	C	
in	in	NPT	in	in	in	in	lb
mm	mm		mm	mm	mm	mm	kg
1-1/4 x 1/2	1.660	1/2 - 14	1.750	1.190	0.625	1.535	0.7
32 x 15	42.2	1/2 - 14	44.5	30.1	15.9	39.0	0.3
1-1/4 x 3/4	1.660	3/4 - 14	1.750	1.190	0.625	1.535	0.7
32 x 20	42.2	3/4 - 14	44.5	30.1	15.9	39.0	0.3
1-1/4 x 1	1.660	1 - 11-1/2	1.900	1.250	0.625	1.535	0.7
32 x 25	42.2	1 - 11-1/2	48.3	31.8	15.9	39.0	0.3
1-1/2 x 1/2	1.900	1/2 - 14	1.750	1.313	0.625	1.775	0.9
40 x 15	48.3	1/2 - 14	44.5	33.3	15.9	45.1	0.4
1-1/2 x 3/4	1.900	3/4 - 14	1.900	1.313	0.625	1.775	0.9
40 x 20	48.3	3/4 - 14	48.3	33.3	15.9	45.1	0.4
1-1/2 x 1	1.900	1 - 11-1/2	1.750	1.375	0.625	1.775	0.9
40 x 25	48.3	1 - 11-1/2	44.5	34.9	15.9	45.1	0.4
2 x 1/2	2.375	1/2 - 14	1.750	1.562	0.625	2.250	1.1
50 x 15	60.3	1/2 - 14	44.5	39.7	15.9	57.2	0.5
2 x 3/4	2.375	3/4 - 14	1.900	1.562	0.625	2.250	1.1
50 x 20	60.3	3/4 - 14	48.3	39.7	15.9	57.2	0.5
2 x 1	2.375	1 - 11-1/2	1.750	1.625	0.625	2.250	1.1
50 x 25	60.3	1 - 11-1/2	44.5	41.3	15.9	57.2	0.5
2-1/2 x 1/2	2.375	1/2 - 14	1.750	1.750	0.625	2.720	1.3
65 x 15	60.3	1/2 - 14	44.5	44.5	15.9	69.1	0.6
2-1/2 x 3/4	2.875	3/4 - 14	1.900	1.750	0.625	2.720	1.3
65 x 20	73.0	3/4 - 14	48.3	44.5	15.9	69.1	0.6
2-1/2 x 1	2.875	1 - 11-1/2	1.900	1.813	0.625	2.720	1.3
65 x 25	73.0	1 - 11-1/2	48.3	46.0	15.9	69.1	0.6

MATERIAL SPECIFICATIONS

FITTING BODY:

- Ductile Iron castings to ASTM A536, Gr. 65-45-12 and or to ASTM A395, Gr. 65-45-15, min. tensile strength 65,000 psi (448 MPa).

THREADS:

- ANSI B1.20.1 NPT or BSP

SURFACE FINISH:

- Standard painted finishes in orange or RAL3000 red.
- Hot dip galvanized (optional)
- Epoxy coatings in RAL3000 red or other colors (optional)

GENERAL NOTES

- Maximum Working Pressure (CWP) listed is the maximum cold water pressure for general piping services tested to ASTM F1476 and or AWWA C606 methods. Figures listed are based on roll- or cut-grooved standard wall carbon steel pipe. For other pipe schedules or pipe materials, contact Shurjoint for additional information.
- Max. End Load is calculated based on the maximum working pressure (CWP).
- Listed and or Approved Pressures are pressure ratings for fire protection systems, tested and approved by various approval bodies. Please always refer to the latest approval data posted on the Shurjoint website.
- Field Joint Test: For one time only the system may be tested hydrostatically at 15. times the maximum working pressure listed (AWWA C606 5.2.3).
- Warning: Piping systems must always be depressurized and drained before attempting disassembly and or removal of any components.
- The 10 Year Limited Warranty applies to manufacturing defects only and does not cover severe service/temperature applications or wear parts.
- Shurjoint reserves the right to change specifications, designs and or standard without notice and without incurring any obligations.