

# 101T-PR

class 125, rising stem, press, gate valve



"Apollo" Press



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

## description

The Apollo Press® model 101T-PR (30 Series) Class 125 Gate Valve with Press connections is a proven combination that provides economical installation and reliable service. The valves are cast, machined, assembled, and tested in South Carolina using proven ASTM quality materials. The rising stem gate valve can reliably be installed in most plumbing and heating systems including building service piping and OEM applications.

## features

- fast, reliable, economical press installation
- Ridgid® XL Press Tool Compatible
- Leak Before Press® Technology
- full port flow
- guided solid lead free\* bronze disc
- adjustable graphite stem packing
- rising stem
- screw-in bonnet
- rugged malleable iron hand wheel
- back seat protection
- made in USA, ARRA compliant

## approvals

- MSS SP-80 - bronze gate, globe, angle & check valves - type 2
- CRN OC14667.5

## performance rating

- maximum pressure: 200 psi (13.8 bar) non-shock
- temperature range: 0°F - 250°F (-18°C - 121°C)

Apollo Press® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service

not intended for potable water

## standard materials list

<b>body</b>	ASTM B62 -C83600 bronze
<b>bonnet</b>	ASTM B62 -C83600 bronze
<b>connector housing</b>	ASTM B16 -C36000 brass
<b>connector o-ring</b>	NSF grade EPDM
<b>stem</b>	ASTM B371 C69400 bronze
<b>disc</b>	ASTM B62 -C83600 bronze
<b>packing</b>	grafoil
<b>hand wheel</b>	malleable iron
<b>nameplate</b>	aluminum

## dimensions

model no.	part no.	size (in.)	height open (in.)	length (in.)	weight (lb.)	cv (gpm)
101T-12-PR	30-003-01PR	1/2"	4.85	3.9	1.3	12.5
101T-34-PR	30-004-01PR	3/4"	5.71	4.3	1.8	24.0
101T-1-PR	30-005-01PR	1"	6.71	4.7	2.6	72.3
101T-114-PR	30-006-01PR	1-1/4"	8.1	5.13	3.8	80.0
101T-112-PR	30-007-01PR	1-1/2"	9.08	6.12	5.4	119.0
101T-2-PR	30-008-01PR	2"	11.28	6.70	8.5	338.0

For liquids the flow coefficient - Cv - expresses the flow capacity in gallons per minute (GPM) of 60°F water with a pressure drop of 1 psi (lb/in<sup>2</sup>).